



STK4703 SERIES	thick film hybrid IC	CIRCUIT DRAWING No.6026
2-CHANNEL 10 TO 50W MIN AF POWER AMP.(DUAL-SUPPLY)		 4029


Features

- AF Output Power STK4773: 10Wmin. STK4793: 15Wmin. STK4803: 20Wmin.
 STK4813: 20Wmin. STK4833: 25Wmin. STK4843: 30Wmin.
 STK4853: 30Wmin. STK4863: 35Wmin. STK4873: 35Wmin.
 STK4893: 40Wmin. STK4913: 50Wmin.
- Contains emitter follower circuit for upgrading.
- Case temperature 125°C is guaranteed, thereby enabling great reduction of heat sink.
- By attaching muting circuit externally, pop noise at the time of power ON/OFF can be rejected.

STK5320 SERIES	thick film hybrid IC	CIRCUIT DRAWING No.6028
2-OUTPUT SERIES REGULATOR FOR VTR APPLICATIONS		 4036 4037 4039


Features

- | | | | | |
|-----------|------------------|------------------|------------------|------------------|
| | STK5321 | STK5322 | STK5324 | STK5325 |
| Output 1: | 9.5±0.1V (1.6A) | 9.5±0.1V (1.6A) | 12.0±0.1V (1.6A) | 12.0±0.1V (1.6A) |
| Output 2: | 12.0±0.3V (2.5A) | 15.0±0.3V (2.5A) | 12.0±0.3V (2.5A) | 14.0±0.3V (2.5A) |
-
- | | | |
|-----------|------------------|------------------|
| | STK5326 | STK5327 |
| Output 1: | 12.0±0.1V (1.6A) | 15.0±0.3V (2.5A) |
| Output 2: | 13.0±0.3V (2.5A) | 13.5±0.3V (1.6A) |
- 2-output/1-package voltage regulator fabricated using Sanyo's original IMST (Insulated Metal Substrate Technology).
 - Provides cutoff function to cut off output voltage by external signal.
 - Output voltages of 2 outputs are set.
 - Small size and excellent cost performance.
 - Package Number: 4036 (STK5324)
 4037 (STK5325, 5326, 5327)
 4039 (STK5321, 5322)

STK5346	thick film hybrid IC	CIRCUIT DRAWING No.6027
2-OUTPUT SERIES REGULATOR FOR VTR APPLICATIONS		 4038

Features

- 2-output/1-package voltage regulator fabricated using Sanyo's original IMST (Insulated Metal Substrate Technology).
- Provides cutoff function to cut off output voltage by external signal.
- Output voltages of 2 outputs are set.
- Small size and excellent cost performance.

STK5352,5353	thick film hybrid IC	CIRCUIT DRAWING No.6029
2-OUTPUT SERIES REGULATOR FOR VTR APPLICATIONS		 4064

Features

- | | | |
|-----------|------------------|------------------|
| | STK5352 | STK5353 |
| Output 1: | 6.0±0.1V (0.5A) | 5.1±0.1V (0.5A) |
| Output 2: | 12.0±0.1V (1.5A) | 12.0±0.1V (1.5A) |
- 2-output/1-package voltage regulator fabricated using Sanyo's original IMST (Insulated Metal Substrate Technology)
 - Contains power supply for microcomputer.
 - Output voltages of 2 outputs are set.
 - Small size and excellent cost performance

This datasheet has been downloaded from:

www.DatasheetCatalog.com

Datasheets for electronic components.