

# Eaton UTG6128PN

Catalog Number: UTG6128PN

Male plug, IP65; UTG6128PN

## General specifications

Product Name	Catalog Number
Eaton Souriau UTG series metal and plastic connector for heavy use	UTG6128PN
	Product Length/Depth
	31.8 mm
Product Height	Product Width
31.4 mm	31.4 mm
Product Weight	
23 g	

## Product specifications

### Shell size

12

### Operating temperature - max

105 °C

### Plug type

Straight Plug

### Coupling type

1/3 Bayonet

### Insert material

Polyamide

### Contact delivery

Not delivered

### Contact type

Crimp

### Degree of protection

IP65

### Number Of Poles

8-pole

### Salt spray

48 hour

### Connector accessory option

Not delivered, to be ordered separately

### Operating temperature - min

-40 °C

### Fitted with:

First mate last break capability(optional)

Last mate first break capability(optional)

### Environmental conditions

RoHS

REACH

Flammability rating UL94 V0

### Connector type

Plug

### Number of cavity #16

8

### Plating

## Resources

### Drawings

[bsa201458003.pdf](#)

Nickel

Contact gender

Pin (Male)

Mating cycles

500

Shell material

Metal & Plastic



Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com  
© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)