

Eaton 170M2668

Catalog Number: 170M2668

Fuse-link, high speed, 250 A, AC 690 V, DIN 00, aR, DIN, IEC, single indicator, live gripping lugs



General specifications

Product Name	Catalog Number
Eaton Bussmann series high speed square body fuse	170M2668
	Model Code
	FUSE 250A 690V 00TN/80 AR UR
UPC	EAN
051712799188	5027590442459
Product Length/Depth	Product Height
100 mm	67 mm
Product Width	Product Weight
30 mm	224 g
Warranty	Compliances
Not Applicable	CE Marked
	RoHS Compliant
Certifications	
IEC Rated	
UL Recognized	

Product specifications

Interrupt rating

200 kAIC

Center-to-center distance of connections

78 mm

Insulated metal gripping lugs (IMGL)

No

Current type

AC

Amperage Rating

250 A

Fuse type

DIN 43653

TN/80 Type T Indicator for Micro

Fuse system (according to IEC 60269)

Other

Fuse size

00

Voltage rating

690 V (IEC), 700 V (UL)

Fuse indicator

Top fuse status indicator

Construction size

00

Clearing (I²T)

42000 at 660 V

Rated voltage AC

690 V

Color

None

Connection

Blade end x blade end

Mounting dimension

M10

Utilization category

aR (accompanied semiconductor protection)

Resources

Catalogs

Bussmann series complete full line catalog no. 1007

Compliance information

CE 170M Size 00, rated 690 Vac, up to 400A

UKCA 170M Size 00, rated 690 Vac, up to 400A

Watt losses

645 W

Type

Fuse

Fuse shape

Square body, slotted offset bolted tags

Breaking capacity

200 kA

Class

Class aR

Pre arc (I2T)

6250

Application

Semiconductor, DC Common bus, DC drives, power converters/rectifiers

Voltage type

AC

Packaging type

Standard



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)