Eaton 120FEE

Catalog Number: 120FEE

Eaton Bussmann series high speed British standard fuse, Double barrel, 120A, 690 VAC/500 VDC (IEC), 700 VAC/500 VDC (UL), Class aR, Breaking capacity 200 kA RMS Sym., 50 kA DC at 500 VDC

General specifications

Product Name Catalog Number

Eaton Bussmann series high speed 120FEE

British standard fuse

UPC

051712830539

EAN Product Length/Depth

5027590429702 94 mm

Product Height Product Width

36 mm 20 mm

Product Weight Warranty

91.6 g Not Applicable

Compliances Certifications

CE Marked RoHS Compliant IEC Rated UL Recognized Designed

and tested to BS88 part 4 IEC 60269-4



Electrical data

Amperage Rating

120 A

Voltage rating

690 V (IEC), 700 V (UL)

Rated voltage AC

690 V

Rated voltage DC

500 V

Interrupt rating

200 kA RMS Sym, 50 kA at 500 Vdc

Class

Class aR

Pre arc (I2T)

540

Clearing (I2T)

1900 at 415 V, 3100 at 660 V

Watt losses

32 W

Product specifications

Application

Semiconductor, DC Common bus, DC drives, power converters/rectifiers

Fuse indicator

None

Compatble Trip indicator/Microswitch

Suitable for

EC-600 Trip indicator kit (indicator + clips)

TI700 Fuse indicator

MAI Microswitch/adaptor

MBI Microswitch/adaptor

Resources

Catalogs

IEC high speed fuse links

Bussmann series complete full line catalog no. 1007

Certification reports

DA-DC-00004682

DA-DC-00004685

Compliance information

UKCA Low voltage fuse-links *AET,*AEET,*AFEE etc

Specifications and datasheets

Eaton Specification Sheet - 120FEE

Technical data sheets

720024 CT, ET, FE, EET, FEE, FM, FMM, MT, MMT fuses



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

Reserved.

Eaton is a registered trademark.

All other trademarks are © 2023 Eaton. All Rights property of their respective owners.



Eaton.com/socialmedia