# Eaton 250FM

# Catalog Number: 250FM

Eaton Bussmann series high speed British standard fuse, Single barrel, 250A, 690 VAC/450 VDC (IEC), 700 VAC/500 VDC (UL), Class aR, Breaking capacity 200 kA RMS Sym., 40 kA DC at 450 VDC (IEC), 50 kA at 500 VDC (UL)

#### General specifications

Product Name

Eaton Bussmann series high speed

British standard fuse

Catalog Number

250FM

UPC

051712833066

Product Length/Depth

EAN

5027590039246

Product Height

45 mm

Product Width

115 mm

46 mm

**Product Weight** 

226 g

Warranty

Not Applicable

Compliances

CE Marked RoHS Compliant

Certifications

UL Recognized IEC Rated Designed and tested to BS88 part 4 IEC 60269-4

UL recognized CCC



## Electrical data

**Amperage Rating** 

250 A

Voltage rating

690 V (IEC), 700 V (UL)

Rated voltage AC

690 V

Rated voltage DC

450 V

Interrupt rating

200 kA RMS Sym (IEC/UL), 40 kA at 450 Vdc (IEC), 50 kA at 500 Vdc (UL)

Class

Class aR

Pre arc (I2T)

5200

Clearing (I2T)

20500

Watt losses

48 W

## **Product specifications**

Application

Semiconductor, DC Common bus, DC drives, power converters/rectifiers

Fuse indicator

None

## Compatble Trip indicator/Microswitch

Suitable for

MC-600 Trip indicator kit (indicator + clips)

TI700 Fuse indicator

MAI Microswitch/adaptor

MBI Microswitch/adaptor

#### Resources

#### Catalogs

IEC high speed fuse links

Bussmann series complete full line catalog no. 1007

Certification reports

DA-DC-00004682

DA-DC-00004685

Compliance information

UKCA Low voltage fuse-links \*AET,\*AEET,\*AFEE etc

Specifications and datasheets

Eaton Specification Sheet - 250FM

Technical data sheets

720024 CT, ET, FE, EET, FEE, FM, FMM, MT, MMT fuses



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

Reserved.

Eaton is a registered trademark.

All other trademarks are © 2023 Eaton. All Rights property of their respective owners.



Eaton.com/socialmedia