Eaton FWC-25A10F

Catalog Number: FWC-25A10F

Eaton Bussmann series FWC high speed cylindrical fuse, 500 Vac/dc (35-800A only), 25A, 200 kAIC Vac, 50 kAIC at 700 Vdc, Non Indicating, High speed fuse, Ferrule end X ferrule end

General specifications

Product Name

Eaton Bussmann series high speed

cylindrical fuse

Catalog Number

FWC-25A10F

UPC

051712796477

EAN Product Length/Depth

5027590420600 38 mm

Product Height Product Width

11 mm 11 mm

Product Weight Warranty

8.8 g Not Applicable

Compliances Certifications
CE Marked CSA Certified
RoHS Compliant UL Recognized



Product specifications Fuse indicator Other Interrupt rating 200 kAIC Vac Construction size 10 x 38 mm Clearing (I2T) 390 Connection Ferrule end x ferrule end Material Ceramic Release characteristic Other **Amperage Rating** 25 A Frequency rating - max 62 Hz Utilization category aR (accompanied semiconductor protection) Watt losses 6 W Fuse type FWC-A10F Accessories BMM Fuse block CHM modular fuse holder Type High speed fuse Fuse shape Cylindrical Breaking capacity 200 kA

Fuse size 10 x 38 mm

Resources

Catalogs

IEC high speed fuse links

Bussmann series complete full line catalog no. 1007

Compliance information

UKCA FWC-*A10F,FWH-*A14F,FWP-*A14F,FWP-*A14FI etc

CE FWC-*A10F,FWH-*A14F,FWP-*A14F,FWP-*A14FI etc

Technical data sheets

720011 FWC

Frequency rating - min

45 Hz

Class

Class aR

Pre arc (I2T)

60

Voltage rating

600 V

Application

Semiconductor, DC Common bus, DC drives, Power converters/rectifiers

Voltage type

AC/DC

Packaging type

Standard



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

Reserved.

Eaton is a registered trademark.

All other trademarks are © 2024 Eaton. All Rights property of their respective owners.



Eaton.com/socialmedia