

Eaton FWH-200B

Catalog Number: FWH-200B

Eaton Bussmann series FWH high speed fuse, 500 Vac/dc (UL), 200A, 200 kAIC at 300 Vdc, 50 kAIC at 300 Vdc, None, High speed fuse, Blade end X blade end, Class aR, Stud, White, Ceramic

General specifications

Product Name	Catalog Number
Eaton Bussmann series high speed cylindrical fuse	FWH-200B
	UPC
	051712795869
EAN	Product Length/Depth
5027590020916	91 mm
Product Height	Product Width
30 mm	30 mm
Product Weight	Warranty
152 g	Not Applicable
Compliances	Certifications
CE Marked	UL Recognized
RoHS Compliant	CSA Certified



Product specifications

Rated voltage DC

500 V

Interrupt rating

200 kAIC at 300 Vdc

50 kAIC at 300 Vdc

Center-to-center distance of connections

74.09 mm

Insulated metal gripping lugs (IMGL)

No

Current type

AC/DC

Mounting method

Stud

Amperage Rating

200 A

Fuse type

FWH-B

Fuse system (according to IEC 60269)

Other

Rated switching capacity

200 kA

Voltage rating

500 Vac, 500 Vdc

Fuse indicator

Non Indicating

Construction size

Other

Clearing (I2T)

8500

Rated voltage AC

500 V

Color

White

Connection

Blade end x blade end

Resources

Catalogs

IEC high speed fuse links

Bussmann series complete full line catalog no. 1007

Specifications and datasheets

Eaton Specification Sheet - FWH-200B

Quantity

1

Material

Ceramic

Mounting dimension

M8

Utilization category

aR (accompanied semiconductor protection)

Watt losses

40 W

Type

High speed fuse

Fuse shape

Center bolted tags

Breaking capacity

200 kA

Class

Class aR

Pre arc (I²T)

1900

Application

Semiconductor, DC Common bus, DC drives, Power converters/rectifiers

Voltage type

AC/DC



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia