

Eaton 280MMT

Catalog Number: 280MMT

Eaton Bussmann series high speed British standard fuse, Double barrel, 280A, 690 VAC/350 VDC (IEC), 700 VAC (UL), Class aR, Breaking capacity 200 kA RMS Sym., 40 kA DC at 350 VDC (IEC)

General specifications

| | |
|---|-------------------------------|
| Product Name | Catalog Number |
| Eaton Bussmann series high speed British standard fuse | 280MMT UPC 051712833394 |
| EAN | Product Length/Depth |
| 5027590039604 | 110 mm |
| Product Height | Product Width |
| 83 mm | 39 mm |
| Product Weight | Warranty |
| 478 g | Not Applicable |
| Compliances | |
| RoHS Compliant CE Marked | |



Electrical data

Amperage Rating

280 A

Voltage rating

690 V (IEC), 700 V (UL)

Rated voltage AC

690 V

Rated voltage DC

350 V

Interrupt rating

200 kA RMS Sym (IEC/UL), 40 kA at 350 Vdc (IEC)

Class

Class aR

Pre arc (I2T)

6600

Clearing (I2T)

47000

Watt losses

47 W

Product specifications

Application

Semiconductor, DC Common bus, DC drives, power converters/rectifiers

Fuse indicator

None

Compatible Trip indicator/Microswitch

Suitable for

MC-700 Trip indicator kit (indicator + clips)

TI700 Fuse indicator

MAI Microswitch/adaptor

MBI Microswitch/adaptor

Resources

Catalogs

[IEC high speed fuse links](#)

[Bussmann series complete full line catalog no. 1007](#)

Certification reports

[DA-DC-00004685](#)

[DA-DC-00004682](#)

Compliance information

[UKCA Low voltage fuse-links *AET,*AEET,*AFEE etc](#)

Specifications and datasheets

[Eaton Specification Sheet - 280MMT](#)

Technical data sheets

[720024 CT, ET, FE, EET, FEE, FM, FMM, MT, MMT fuses](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)