

Eaton 315MMT

Catalog Number: 315MMT

Eaton Bussmann series high speed British standard fuse, Double barrel, 315A, 690 VAC/350 VDC (IEC), 700 VAC (UL), Class aR, Breaking capacity 200 kA RMS Sym., 40 kA DC at 350 VDC (IEC)

General specifications

Product Name	Catalog Number
Eaton Bussmann series high speed British standard fuse	315MMT
	UPC
	051712833837
EAN	Product Length/Depth
5027590043526	110 mm
Product Height	Product Width
83 mm	39 mm
Product Weight	Warranty
467 g	Not Applicable
Compliances	Certifications
CE Marked RoHS Compliant	IEC Rated UL Recognized Designed and tested to BS88 part 4 IEC 60269-4 UL recognized



Electrical data

Amperage Rating

315 A

Voltage rating

690 V (IEC), 700 V (UL)

Rated voltage AC

690 V

Rated voltage DC

350 V

Interrupt rating

200 kA RMS Sym (IEC/UL), 40 kA at 350 Vdc (IEC)

Class

Class aR

Pre arc (I2T)

8600

Clearing (I2T)

62000

Watt losses

51 W

Product specifications

Application

Semiconductor, DC Common bus, DC drives, power converters/rectifiers

Fuse indicator

None

Compatible Trip indicator/Microswitch

Suitable for

MC-700 Trip indicator kit (indicator + clips)

TI700 Fuse indicator

MAI Microswitch/adaptor

MBI Microswitch/adaptor

Resources



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia