Product specifications

Eaton 200MT

Catalog Number: 200MT

Eaton Bussmann series high speed British standard fuse, Single barrel, 200A, 690 VAC/350 VDC (IEC), 700 VAC (UL), Class aR, Breaking capacity 200 kA RMS Sym., 40 kA DC at 350 VDC (IEC)

General specifications

Product Name

Eaton Bussmann series high speed

British standard fuse

200MT

UPC

051712832229

Product Length/Depth

Catalog Number

EAN

5027590466554

Product Height

39 mm

Product Weight

236 g

Warranty

39 mm

110 mm

Not Applicable

Product Width

Compliances **CE Marked**

RoHS Compliant

Certifications

IEC Rated

UL Recognized

Designed and tested to BS88 part 4

IEC 60269-4 UL recognized



Electrical data

Amperage Rating

200 A

Voltage rating

690 V (IEC), 700 V (UL)

Rated voltage AC

690 V

Rated voltage DC

350 V

Interrupt rating

200 kA RMS Sym (IEC/UL), 40 kA at 350 Vdc (IEC)

Class

Class aR

Pre arc (I2T)

6000

Clearing (I2T)

40000 at 415 V, 58000 at 660 V

Watt losses

27 W

Product specifications

Application

Semiconductor, DC Common bus, DC drives, power converters/rectifiers

Fuse indicator

None

Compatble Trip indicator/Microswitch

Suitable for

MC-700 Trip indicator kit (indicator + clips)

TI700 Fuse indicator

MAI Microswitch/adaptor

MBI Microswitch/adaptor

Resources

Catalogs

IEC high speed fuse links

Bussmann series complete full line catalog no. 1007

Certification reports

DA-DC-00004685

DA-DC-00004682

Compliance information

 ${\sf UKCA\ Low\ voltage\ fuse-links\ *AET,*AEET,*AFEE\ etc}$

Specifications and datasheets

Eaton Specification Sheet - 200MT

Technical data sheets

720024 CT, ET, FE, EET, FEE, FM, FMM, MT, MMT fuses



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

Reserved.

Eaton is a registered trademark.

All other trademarks are © 2023 Eaton. All Rights property of their respective owners.



Eaton.com/socialmedia