

中型钮子开关 Medium Toggle Switch

技术特性 Specifications

- 规格 Rating: ()10A 125VAC;6A 250VAC
(A)15A 125VAC;10A 250VAC
(AA)20A 125VAC;15A 250VAC
- 接触电阻 Contact Resistance: 50mΩ max
- 绝缘电阻 Insulation Resistance: 500VDC 1000MΩ Min
- 耐电压 Dielectric Strength: 1500VAC, 1Minute
- 操作温度 Operating Temperature: -25℃~ +85℃
- 电气寿命 Electrical Life: ≥10,000 Cycles

选型说明 How to order

KN3 C - 1 02 A P E - BN
 钮子外壳类型 | 刀数 | 电路特性 | 规格 | 端子种类 | 手柄种类 | 底座颜色
 Housing shape | Poles | Switch Function | Rating | Terminal options | Handle options | Housing color

A	1	01	A	()	()	BK
B	2	02		()	()	BN
C	3	11		()	()	OG
D	3	12		()	()	
E	4	03		()	()	
		13		()	()	
		23		()	()	

() : 回弹指示
Indicates Momentary

Terminal options:
 Screw Terminal () | Solder Terminal (S)
 PC Terminal (P) | Press Terminal (T)
 Hitch Terminal (R)

Handle options:
 () | (D) | (E) | (C) | (L)

Housing color:
 BK 黑色 Black
 BN 棕色 Brown
 OG 橘黄 Orange

防水帽 Water proof cap

WPC-06 M12X0.75 M12X1.0		WPC-08 M12X0.75 M12X1.0		WPC-11 M12X0.75		WPC-12 M12X0.75	
--------------------------------------	--	--------------------------------------	--	---------------------------	--	---------------------------	--

	KN3C-101 ON-OFF KN3C-111 OFF-(ON) SPST 2P			
	KN3C-102 ON-ON KN3C-112 ON-(ON) KN3C-103 ON-OFF-ON KN3C-113 ON-OFF-(ON) KN3C-123 (ON)-OFF-(ON) SPDT 3P			
	KN3C-201 ON-OFF KN3C-211 OFF-(ON) DPST 4P			
	KN3C-202 ON-ON KN3C-212 ON-(ON) KN3C-203 ON-OFF-ON KN3C-213 ON-OFF-(ON) KN3C-223 (ON)-OFF-(ON) DPDT 6P			
	KN3C-302 ON-ON KN3C-303 ON-OFF-ON 3PDT 9P			
	KN3C-402 ON-ON KN3C-403 ON-OFF-ON 4PDT 12P			