



# ALL NEW DESIGNED BLUETOOTH CLAMP METER

## DCM7000BT DCM8500PV

- Industrial, HVAC & Solar PV Application (DCM8500PV)
- 6,000 count large white LED backlight display
- DC 600mV measurement for sensors or other application
- DC  $\mu$ A for flame rod testing
- Inrush Current measurement (100ms)
- Special designed LoZ(Low Impedance) feature to prevent false reading caused by ghost voltages (DCM7000BT)



DCM7000BT



DCM8500PV



# All New Designed Bluetooth Clamp Meter



**DCM7000BT**

**DCM8500PV**

## General

Display	6000 counts	6000 counts
Backlight	●	●
MIN/MAX	●	●
Hig Frequency Rejection	●	●
Auto Power Off	●	●
Data Logger	4000 data	4000 data
Dimensions	62x240x41mm	62x240x41mm
Size of JAW	37mm	37mm
Weight (including battery)	430g	430g

## Specification

## Range

DC mV	600mV	600mV
DC Voltage	600V/1000V	600V/1000V
AC Voltage	600V/1000V	600V/1000V
PV DC Voltage	-	600V/2000V
PV AC Voltage	-	600V/1500V
AC/DC AC $\mu$ A	400 $\mu$ A /4000 $\mu$ A	400 $\mu$ A /4000 $\mu$ A
DC Current	-	60A/600V
AC Current	60A/600V	60A/600V
Flexible Current Probe	-	300A/3000V
Frequency	100Hz/1000Hz/10kHz	100Hz/1000Hz/10kHz
Resistance	600 $\Omega$ /6k $\Omega$ /60k $\Omega$ /600k $\Omega$	600 $\Omega$ /6k $\Omega$ /60k $\Omega$ /600k $\Omega$
Diode	1.5V	1.5V
Capacitance	100 $\mu$ F/1000 $\mu$ F	100 $\mu$ F/1000 $\mu$ F
Temperature	-40°C ~ -400°C	-40°C ~ -400°C

## Order Info

SKU NO.	KPSDCM7000BTCBINT	KPSDCM8500PVCBINT
EAN Code	8435394784687	8435394784694
UPC Code	810053676592	810053676608
Amount / Box	20 PCS	20 PCS

www.kps-intl.com