

ENH 250W 120V 24/CS 1/SKU



Product features and benefits

- Robust construction for reliable, lasting performance
- Consistent color over the life of the lamps
- Instant on and nearly constant luminous flux over the life of the lamp
- Broad product portfolio supporting the stage and studio markets
- Dimmable with traditional amber shift

Areas of application

- Stage and theatre
- Studio, TV and film
- Professional Photography
- Club & Disco

Technical data

General product information

Product Number	54986
Product Name	ENH 250W 120V 24/CS 1/SKU
Ordering Abbreviation	ENH 250W 120V 24/CS 1/SKU
Brand Name	OSRAM
Application	Projector - Slide
Product Remark	– s (Operating Position) = Vertical, base down – Lumens refers to screen lumens.

Electrical data

Nominal Wattage	250 W
Nominal Voltage	120 V
Type of Current	AC

Light technical data

Luminous Flux	340 lm
Working Distance a (in)	5.948 in
Working Distance a (mm)	152.5 mm
Color Rendering Index	100
Average Rated Life	175 h


Physical attributes

Maximum Overall Length (in)	1.735 in
Maximum Overall Length (mm)	44.5 mm
Length l (in)	1.735 in
Length l (mm)	44.5 mm
Length l max. (in)	1.735 in
Length l max. (mm)	44.5 mm
Diameter d (in)	2.008 in
Diameter d (mm)	51.00 mm
Reflector Coating	51.00

Additional product data

Operating Position	s 90
Class	C (gas)

Product datasheet



Packaging Information

Product number	EAN/UPC	Packaging	Quantity	Outside dimensions l x w x h	Gross weight
54986	4050300349930	Folding box (SKU)	1	1.7 in x 1.7 in x 2.2 in	0.1 lb
54986	4050300349947	Shipping box (Case)	24	7.6 in x 5.3 in x 6 in	2.1 lb

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

OSRAM does not accept liability for errors, changes and omissions.