



<b>Symbol:</b>	AX-3010DS
<b>Manufacturer:</b>	AXIOMET
<b>Product groups:</b>	1-channel power supplies

## Product specifications

<b>Type of power supply:</b>	laboratory
<b>Kind of display used:</b>	2x LCD 3 digits
<b>Number of channels:</b>	1
<b>Output voltage:</b>	0...30 V DC
<b>Output current:</b>	0...10 A
<b>Voltage stabilisation:</b>	$\leq 1\% + 10\text{mV}$
<b>Current stabilisation:</b>	$\leq 1\% + 5\text{mA}$
<b>Voltage (regulated) ripple and noise:</b>	$\leq 200\text{mVpp}$

## Product card AX-3010DS

---

<b>Dimensions:</b>	80x160x205 mm
<b>Weight:</b>	1.5 kg
<b>Power supply:</b>	230V AC 50/60Hz
<b>Kind of power supply:</b>	switched-mode, single-channel
<b>Protection:</b>	anti-overload
<b>Measuring instrument features:</b>	<ul style="list-style-type: none"><li>• simultaneous voltage and current readout</li><li>• voltage and current stepless adjustment</li><li>• coarse and precise voltage and current adjustment</li></ul>
<b>Plug variant:</b>	EU

## Additional information

<b>Gross weight:</b>	2.217 kg
----------------------	----------