



Klemmsan®

306221 YBK 2,5

2,5mm², spring type, 1 input 1 output feed through terminal block, Insulation material PA, Blue

General Product Information	Insulating material	PA
	Inflammability class acc. to UL 94	V2
	Packing Unit	100
	Weight (g)	—
Dimensions	Width	5 mm
	Length	51 mm
	Height (MR 32)	— mm
	Height (MR 35x7.5)	35.5 mm
TSE / CE Technical Data	Nominal Voltage	750 V ~
	Nominal Current	24 A
	Cross Section	2.5 mm ²
	Norm	EN60947-7-1
VDE Technical Data	Nominal Voltage	— V ~
	Nominal Current	— A
	Cross Section	2.5 mm ²
	VDE Norm	—
UL / CSA Technical Data	Nominal Voltage	600 V ~
	Nominal Current	20 A
	Cross Section	AWG/22-12
ATEX Technical Data	Nominal Voltage	— V ~
	Nominal Current	— A
	Cross Section	2.5
Connection Data	Minimum solid strand cross section	0.5 mm ²

Maximum solid Strand cross section	4 mm ²
Minimum fine Strand cross section	0.5 mm ²
Maximum fine strand cross section	2.5 mm ²
AWG Conductor Range	22-12
Connection Type	spring/yaylı
Insulation Stripping length	10 mm
Tightening torque	— Nm



Ukrayna Uygunluk Sertifikası - Ukrayna Uygunluk Sertifikası

Avrupa standartlarına uygunluk belgesi - CE Certificate

Avrupa standartlarına uygunluk belgesi - UL Certificate

Rusya Onaylı Denizcilik Sertifikası - Rusya Denizcilik Certificate

LAPEM - RETIE Sertifikası - LAPEM - Retie Certificate

Order Info

	306220	2,5mm ² ,spring type,1 input 1 output feed through terminal block,Insulation material PA,Beige
	306221	2,5mm ² ,spring type,1 input 1 output feed through terminal block,Insulation material PA,Blue
	306222	2,5mm ² ,spring type,1 input 1 output feed through terminal block,Insulation material PA,Green
	306223	2,5mm ² ,spring type,1 input 1 output feed through terminal block,Insulation material PA,Yellow
	306224	2,5mm ² ,spring type,1 input 1 output feed through terminal block,Insulation material PA,Red
	306229	2,5mm ² ,spring type,1 input 1 output feed through terminal block,Insulation material PA,Grey
	306225	2,5mm ² ,spring type,1 input 1 output feed through terminal block,Insulation material PA,Black
	306226	2,5mm ² ,spring type,1 input 1 output feed through terminal block,Insulation material PA,White
	306227	2,5mm ² ,spring type,1 input 1 output feed through terminal block,Insulation material PA,Orange
	306228	2,5mm ² ,spring type,1 input 1 output feed through terminal block,Insulation material PA,Brown