

# 104182300000

## Light dependent relay 12 - 16 A



This image is for illustrative purposes only and therefore may not represent the exact product code. Colours may vary.

### Technical description:

Light dependent relays - pole or wall mounting, single output, live switching - 1 NO 16 A, 16 A, AC supply version, nominal voltage 230 V, operating from 0.8 to 1.1 V, rated power 2 VA, ambient temperature from -30 to +70 °C

[BROWSE PRODUCT PAGE](#)

### Technical Features:

<b>Commercial Description:</b>	Light dependent relay for the ON/OFF control of lamps according to the level of ambient brightness. Equipped with 1 x NO 16A contact for lamp disconnect in one (L) pole. Adjustable sensitivity from 1 to 80 lux.
<b>Contact configuration:</b>	1 NO
<b>Dimensions:</b>	58.6x110.6x36.8 mm
<b>Protection category:</b>	IP 54
<b>Rated contact voltage:</b>	230 V AC
<b>Rated current (contacts):</b>	16
<b>Supply:</b>	AC supply version
<b>Type of installation:</b>	Pole or wall mounting, single output, live switching - 1 NO 16 A
<b>Certifications and quality approvals (according to type):</b>	   

The information, technical details, data and features contained in this document are subject to change or modification at any time. It is for information purposes only and does not form the basis of a contract.

### Need more information?

[Contact our sales](#) [Find a dealer](#)