


RF-F BF-F GF-F



* Material: Polycarbonate type PC10500AC certified EN45545-2

FEMALE DISCONNECT TERMINALS

for Copper conductors

Recommended crimping tools are shown on pages 124 to 151, 192, 257.

Polycarbonate* insulated terminals partially reinforced with Copper sleeve


Conductor Size sqmm (AWG)	Type	Tab Size mm	Quantity Box/Bag
0,25÷1,5 (22÷16)	RF-F305	2,8 x 0,5	3.000/100
	RF-F308*	2,8 x 0,8	3.000/100
	RF-F405	4,8 x 0,5	2.500/100
	RF-F408	4,8 x 0,8	2.500/100
1,5÷2,5 (16÷14)	RF-F608	6,35 x 0,8	2.500/100
	BF-F405	4,8 x 0,5	2.500/100
	BF-F408	4,8 x 0,8	2.500/100
4÷6 (12÷10)	BF-F608	6,35 x 0,8	1.500/100
	GF-F608	6,35 x 0,8	1.000/100

Polycarbonate* fully insulated terminals partially reinforced with Copper sleeve

Conductor Size sqmm (AWG)	Type	Tab Size mm	Quantity Box/Bag
0,25÷1,5 (22÷16)	RF-F305P	2,8 x 0,5	2.000/100
	RF-F308P*	2,8 x 0,8	2.000/100
	RF-F405P	4,8 x 0,5	1.500/100
	RF-F408P	4,8 x 0,8	1.500/100
1,5÷2,5 (16÷14)	RF-F608P	6,35 x 0,8	1.000/100
	BF-F405P	4,8 x 0,5	1.500/100
	BF-F408P	4,8 x 0,8	1.500/100
4÷6 (12÷10)	BF-F608P	6,35 x 0,8	1.000/100
	GF-F608P	6,35 x 0,8	800/100



RF-M BF-M GF-M



* Material: Polycarbonate type PC10500AC certified EN45545-2

MALE DISCONNECT TERMINALS

for Copper conductors

Recommended crimping tools are shown on pages 124 to 151, 192, 257.

Polycarbonate* insulated terminals partially reinforced with Copper sleeve


Conductor Size sqmm (AWG)	Type	Tab Size mm	Quantity Box/Bag
0,25÷1,5 (22÷16)	RF-M608	6,35 x 0,8	3.000/100
1,5÷2,5 (16÷14)	BF-M608	6,35 x 0,8	2.000/100
4÷6 (12÷10)	GF-M608	6,35 x 0,8	1.000/100

Polycarbonate* fully insulated terminals partially reinforced with Copper sleeve

Conductor Size sqmm (AWG)	Type	Tab Size mm	Quantity Box/Bag
0,25÷1,5 (22÷16)	RF-M608P	6,35 x 0,8	1.000/100
1,5÷2,5 (16÷14)	BF-M608P	6,35 x 0,8	800/100



RF-FM BF-FM RF-B BF-B



* Material: Polycarbonate type PC10500AC certified EN45545-2

MALE/FEMALE

for Copper conductors

Recommended crimping tools are shown on pages 124 to 151, 192, 257.

Polycarbonate* insulated terminals partially reinforced with Copper sleeve

Conductor Size sqmm (AWG)	Type	Tab Size mm	Quantity Box/Bag
0,25÷1,5 (22÷16)	RF-FM608	6,35 x 0,8	1.000/100
1,5÷2,5 (16÷14)	BF-FM608	6,35 x 0,8	1.000/100

BULLET AND SOCKET

for Copper conductors

Polycarbonate* insulated terminals partially reinforced with Copper sleeve

Conductor Size sqmm (AWG)	Type	Ø mm	Quantity Box/Bag
0,25÷1,5 (22÷16)	RF-BM4*	4,0	2.500/100
	RF-BF4*	3,95	800/100
1,5÷2,5 (16÷14)	BF-BM5*	5,0	2.000/100
	BF-BF5*	4,95	800/100



*Not UL approved