

## Joint Connectors - Heat Shrinking Insulation

Tinned copper joint with a heat-shrinking Insulation and internal hot-melt adhesive for waterproofing joints



### Features and benefits

- Effective sealing and insulation of electrical connections


### Applications

- Waterproofing joints in the connection of cables

### Technical data

Conductor material	electrolytic tinned copper (purity grade 99.9%)
Insulation material	cross-linked polyolefin
Halogen	absent
Shrinkage temperature	100°C
Working temperature	-55°C ÷ 125°C
Dielectric strength	30 kV/mm

**HALOGEN FREE**



### JOINT CONNECTORS - HEAT SHRINKING INSULATION

Description	Cable section (mm²)	Cable section (AWG)	Length (mm)	ø seat (mm)	Color	Pack (pcs.)	Code
			A	B			
Joint connectors heat shrinking insulation 0,25÷1,5	0,25 ÷ 1,5	22 ÷ 16	36	5,4	●	100	<b>11221140</b>
Joint connectors heat shrinking insulation 1,5÷2,5	1,5 ÷ 2,5	16 ÷ 14	36	5,8	●	100	<b>11221250</b>
Joint connectors heat shrinking insulation 4÷6	4 ÷ 6	12 ÷ 10	41	6	●	100	<b>11221465</b>

**Hand tools for terminals**  
from page 190