

Technical data sheet

Actuator sensor interface · M12 - connector

Field wireable connector, M12 straight

Female - A coded

Screw terminal



Identification

Type	KUGK-M12 4POL. SK PG7
Part No.	490011

Product version

Datasheet version	00
-------------------	----

General

Design	M 12 female straight
Form male 1	M 12 female straight
Rated insulation voltage	2500 V
Test voltage	2950 V
Degree of pollution	3
Insulation resistance	>10000 M Ω
Contact resistance	<3 m Ω
Flamability according to UL 94	HB
Protection class	IP67
Housing material	PA
Color of the housing	black
Color	black
Contact material	CuZn, gold-plated
Thread material	CuZn nickel-plate
Mounting	Breakaway torque 0.4 Nm
Cable diameter	4 mm – 6 mm

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park
Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU
Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2
www.lutze.com • sales.gb@lutze.co.uk

Germany: Friedrich Lütze GmbH

Postfach 12 24 (PLZ 71366) • Bruckwiesenstraße 17-19 • D-71384 Weinstadt
Tel. +49 (0)7151 6053-0 • Fax +49 (0)7151 6053-277(-288)
www.luetze.de • info@luetze.de

09.11.2021 • Subject to technical modification

Part No. 490011 • Datasheet version: 00

page 1 of 3



SYSTEMATIC TECHNOLOGY

Technical data sheet

Actuator sensor interface · M12 - connector

Storage temperature range	-40 °C ... +90 °C
Temperature range connector	-25 °C ... +85 °C
Mechanical service life	>100 insertion cycles
Cross-section, metric	0.75 mm ²
Connection type	Screw terminal max. 0.75 mm ²
Weight/unit	0.04 kg
PU (units)	1

Technical data

Rated voltage U _N	AC/DC 24 V
Operating voltage max.	250 V
Rated current	4 A
Pole number	4
Coding	A

Certifications/Standards

Certifications	cURus (E224249)
----------------	-----------------

Accessories

Accessories

matching cables:

117243 | SU TR AS PUR 3×0,34 UL | Jacket material: PUR


117244 | SU TR AS PUR 4×0,34 UL | Jacket material: PUR

117245 | SU TR AS PUR 5×0,34 UL | Jacket material: PUR


117246 | SU TR AS PUR 6×0,34 UL | Jacket material: PUR

117242 | SU TR AS PUR 8×0,25 UL | Jacket material: PUR

Dimensions



Mounting diagram



Technical data sheet

Actuator sensor interface · M12 - connector

Pin layout

