

Technical data sheet - TOP-T-P gray

Cable fittings and accessories



Identification	Type	TOP-T-P PG21
	Part-No.	600665

Use/Application/Characteristics

Characteristics	<ul style="list-style-type: none">• – PG –• Cable fitting with hexagon base• Strain relief and seal
-----------------	---

Technical data

Clamping range D	13 – 18 mm
Approvals	UL
Temperature range	-20 °C ... +100 °C
Protection class	IP68
	Up to 5 bar
Thread form	PG
Thread G	PG 21
SW	33 mm
L1	11 mm

Construction

Description	TOP-T-P PG21
Material	PA 6.6-V-2
Material sealing ring	Neoprene
Color	grey RAL 7001

23.08.2019 – Subject to technical modification

Part-No. 600665

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA
Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223
www.lutze.com • info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park
Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU
Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2
www.lutze.com • sales.gb@lutze.co.uk




SYSTEMATIC TECHNOLOGY

Technical data sheet - TOP-T-P gray

General

PU 25 piece

Dimensions



Symbols



23.08.2019 – Subject to technical modification

Part-No. 600665

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA
Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223
www.lutze.com • info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park
Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU
Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2
www.lutze.com • sales.gb@lutze.co.uk