

# Technical data sheet - Metal fitting TOP-T

Cable fittings and accessories



<b>Identification</b>	Type	TOP-T MS M12x1,5
	Part-No.	600701
<b>Use/Application/Characteristics</b>		
Characteristics	<ul style="list-style-type: none"><li>• Cable fitting with hexagon base</li><li>• Strain relief</li><li>• Gasket and O-Ring</li></ul>	
<b>Technical data</b>		
Clamping range D	3 – 6.5 mm	
Temperature range	-30 °C ... +100 °C	
Protection class	IP68	
	Up to 5 bar	
Thread form	metric	
Thread G	M 12x1.5	
SW 1	14 mm	
SW 2	14 mm	
L	25 mm	
L1	5 mm	
<b>Construction</b>		
Description	TOP-T MS M12x1.5	
Material	Brass nickel-plated	
Material O-ring	NBR	

16.04.2019 – Subject to technical modification

Part-No. 600701

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA  
Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223  
www.lutze.com • info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park  
Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU  
Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2  
www.lutze.com • sales.gb@lutze.co.uk



SYSTEMATIC TECHNOLOGY


# Technical data sheet - Metal fitting TOP-T

Material sealing ring CR

## General

PU 100 piece

## Dimensions



16.04.2019 – Subject to technical modification

Part-No. 600701

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA  
Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223  
www.lutze.com • info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park  
Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU  
Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2  
www.lutze.com • sales.gb@lutze.co.uk