

Technical data sheet - Metal fitting TOP-T

Cable fittings and accessories



Identification	Type	TOP-T MS PG7
	Part-No.	600710
Use/Application/Characteristics		
Characteristics	<ul style="list-style-type: none">• Cable fitting with hexagon base• Strain relief• Gasket and O-Ring	
Technical data		
Clamping range D	3 – 6.5 mm	
Temperature range	-20 °C ... +100 °C	
Protection class	IP68	
	Up to 5 bar	
Thread form	PG	
Thread G	PG 7	
SW 1	14 mm	
SW 2	14 mm	
L	24 mm	
L1	5 mm	
Construction		
Description	TOP-T MS PG7	
Material	Brass nickel-plated	
Material O-ring	NBR	

16.04.2019 – Subject to technical modification

Part-No. 600710

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA
Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223
www.lutze.com • info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park
Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU
Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2
www.lutze.com • sales.gb@lutze.co.uk



SYSTEMATIC TECHNOLOGY


Technical data sheet - Metal fitting TOP-T

Material sealing ring CR

General

PU 100 piece

Dimensions



16.04.2019 – Subject to technical modification

Part-No. 600710

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA
Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223
www.lutze.com • info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park
Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU
Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2
www.lutze.com • sales.gb@lutze.co.uk



SYSTEMATIC TECHNOLOGY