

Technical data sheet

Load monitoring · LOCC-Box Accessories

LOCC-Box end block



Identification

Type LOCC-Box-EB 7-6436
Part No. [716436](#)

Product version

Hardware revision 2.0
Datasheet version 02

General

Accessories End terminal
Housing material PA 6.6 (UL 94 V-0, NFF I2, F2)
Mounting DIN rail mountable TS35 (EN 60715)
Degree of protection IP20 (only as complete system with power terminal and end block)
Installation position Any
Dimensions (w × h × d) 10.0 mm × 110.0 mm × 62.0 mm
Weight/unit 0.01 kg
PU (units) 2

General ambient conditions

Operation temperature range -25 °C ... +50 °C
Storage temperature range -40 °C ... +85 °C
Relative air humidity 10 % – 95 %, without condensation
Vibration resistance 4 g acc. to EN 60068-2-6
Shock resistance 15 g acc. EN 60068-2-27

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park
Sandy Way, Amington · GB-Tamworth, Staffs B77 4DU
Tel. +44 (0)1827 31333-0 · Fax +44 (0)1827 31333-2
www.lutze.com · sales.gb@lutze.co.uk

Germany: Friedrich Lütze GmbH

Postfach 12 24 (PLZ 71366) · Bruckwiesenstraße 17-19 · D-71384 Weinstadt
Tel. +49 (0)7151 6053-0 · Fax +49 (0)7151 6053-277(-288)
www.luetze.de · info@luetze.de

09.12.2022 · Subject to technical modification

Part No. [716436](#) · Datasheet version: 02

page 1 of 2



SYSTEMATIC TECHNOLOGY

Technical data sheet

Load monitoring · LOCC-Box Accessories

Certifications/Standards

Certifications	cULus (E135145)
Standards	UL 60947-5-1
	DNVGL-CG-0339
	Temperature Class D – not certified
	Humidity Class B – not certified
	Vibration Class B – not certified
	Enclosure Class A – not certified

Dimensions

